

	13/11/2014 13:22h	13/11/2014 21:10h	14/11/2014 11:45h	14/11/2014 21:10h
Uptime:	1 day, 0:43:32	1 day, 8:25:56	1 day, 23:09:46	2 days, 8:32:27
DSL Type:	ITU-T G.992.1	ITU-T G.992.1	ITU-T G.992.1	ITU-T G.992.1
Bandwidth (Up/Down) [kbps/kbps]:	448 / 7,776	448 / 7,776	448 / 7,776	448 / 7,776
Data Transferred (Sent/Received) [MB/MB]:	52.54 / 907.21	81.91 / 1.16	88.71 / 1.17	104.11 / 1.50
Output Power (Up/Down) [dBm]:	12.3 / 19.9	12.3 / 19.9	12.3 / 19.9	12.3 / 19.9
Line Attenuation (Up/Down) [dB]:	12.0 / 19.5	12.0 / 19.5	12.0 / 19.5	12.0 / 19.5
SN Margin (Up/Down) [dB]:	29.0 / 6.1	29.0 / 6.1	29.0 / 6.1	29.0 / 6.2
System Vendor ID (Local/Remote):	TMMB / ----	TMMB / ----	TMMB / ----	TMMB / ----
Chipset Vendor ID (Local/Remote):	BDCM / TSTC	BDCM / TSTC	BDCM / TSTC	BDCM / TSTC
Loss of Framing (Local/Remote):	0 / -	0 / -	0 / -	0 / -
Loss of Signal (Local/Remote):	0 / -	0 / -	0 / -	0 / -
Loss of Power (Local/Remote):	0 / -	0 / -	0 / -	0 / -
Loss of Link (Remote):	-	-	-	-
Error Seconds (Local/Remote):	90 / -	119 / -	161 / -	186 / -
FEC Errors (Up/Down):	1 / 0	1 / 0	3 / 0	3 / 0
CRC Errors (Up/Down):	1 / 98	1 / 128	1 / 178	1 / 205
HEC Errors (Up/Down):	- / 201	- / 259	- / 341	- / 385